

# Water jacker wood burning stove K6 Ø 130 8 kW

SKU: KOZA/K6/130/PW/W EAN: 5901350060193

**€859.81**



## Technical data

### General data

|                              |                   |
|------------------------------|-------------------|
| Rated output (kW)            | <b>8</b>          |
| Heating power range (kW)     | <b>7.0 - 11.0</b> |
| Heating efficiency (%)       | <b>70</b>         |
| Exhaust gas temperature (°C) | <b>320</b>        |
| Max length of logs (cm)      | <b>35</b>         |
| Color                        | <b>Black</b>      |
| Self Closure                 | <b>No</b>         |
| Additional equipment         | <b>Boiler</b>     |
| Door opening direction       | <b>Left</b>       |
| Materials                    | <b>Cast iron</b>  |
| Flue outlet diameter (mm)    | <b>130</b>        |

### Energetic efficiency

|                                                    |             |
|----------------------------------------------------|-------------|
| Energy class                                       | <b>A</b>    |
| Energy efficiency index (EEI)                      | <b>91.5</b> |
| Seasonal Heating efficiency (%)                    | <b>60</b>   |
| Moc cieplna do ogrzewania pomieszczeń (kW)         | <b>6.5</b>  |
| Average power from water (kW)                      | <b>1.5</b>  |
| CO emissions (at 13% O <sub>2</sub> ) ≤ given in % | <b>0.11</b> |
| Emisja CO (mg/m <sup>3</sup> )                     | <b>1338</b> |
| Dust emission (mg/Nm <sup>3</sup> )                | <b>22</b>   |
| Emisja NO <sub>x</sub> (mg/Nm <sup>3</sup> )       | <b>100</b>  |
| Emisja OGC (mg/Nm <sup>3</sup> )                   | <b>57</b>   |

## Certifications / Compliance

Meets requirements **Ecodesign**

## Additional information

Design features

**Ashpan**

Front type

**Cast iron front with ceramic glass**

Type of fuel

**Seasoned deciduous wood (humidity ≤20%)**

EAN

**5901350060193**

## Physical parameters

Width (cm) **57.8**

Height (cm) **66.8**

Depth (cm) **49**

Weight (kg) **120**

